


1112-Nut with connecting thread



select	Inquiry	Label	Ball diameter [mm]	No. of starts	Static load capacity [kN]	Friction torque FROM [Ncm]	Friction torque TO [Ncm]	Thread length [mm]	Diameter for pin wrench [mm]	Thread diameter [mm]	Accuracy	Ball circles	Overall length [mm]	dN [mm]	P [mm]	Nominal stroke [mm]	D1 [mm]	L [mm]	Dynamic load capacity [kN]	Series	Shaft style	Thread length [mm]	Preload/backlash free/with backlash
1112/0,5.3.44.85	3	0,5	20	8,5	15	0,09	1112	B	44	85	1x2	0,6	1	0,09	1,0	1,0	5		M6	P	backlash free		
1112/0,5.3.64.105	3	0,5	40	8,5	15	0,09	1112	B	64	105	1x2	0,6	1	0,09	1,0	1,0	5		M6	P	backlash free		
1112/0,5.3.76.90	3	0,5	50	8,5	15	0,09	1112	A	76	90	1x2	0,6	1	0,09	1,0	1,0	5		M6	P	backlash free		
1112/0,5.3.94.135	3	0,5	70	8,5	15	0,09	1112	B	94	135	1x2	0,6	1	0,09	1,0	1,0	5		M6	P	backlash free		
1112/0,5.5.125.165	5	0,5	100	12,5	19	0,17	1112	B	125	165	1x3	0,6	1	0,24	1,5	1,5	6	2	M10x1	P	backlash free		
1112/0,5.5.65.105	5	0,5	40	12,5	19	0,17	1112	B	65	105	1x3	0,6	1	0,24	1,5	1,5	6	2	M10x1	P	backlash free		
1112/0,5.5.90.110	5	0,5	60	12,5	19	0,17	1112	A	90	110	1x3	0,6	1	0,24	1,5	1,5	6	2	M10x1	P	backlash free		
1112/0,5.5.95.135	5	0,5	70	12,5	19	0,17	1112	B	95	135	1x3	0,6	1	0,24	1,5	1,5	6	2	M10x1	P	backlash free		
1112/0,5.8.110.168	8	0,5	70	16,5	21	0,40	1112	B	110	168	1x3	0,6	1	0,50	2,0	2,0	8	3	M14x1	P	backlash free		
1112/0,5.8.140.198	8	0,5	100	16,5	21	0,40	1112	B	140	198	1x3	0,6	1	0,50	2,0	2,0	8	3	M14x1	P	backlash free		
1112/0,5.8.145.170	8	0,5	100	16,5	21	0,40	1112	A	145	170	1x3	0,6	1	0,50	2,0	2,0	8	3	M14x1	P	backlash free		
1112/0,5.8.190.248	8	0,5	150	16,5	21	0,40	1112	B	190	248	1x3	0,6	1	0,50	2,0	2,0	8	3	M14x1	P	backlash free		
1112/0,5.8.245.270	8	0,5	200	16,5	21	0,40	1112	A	245	270	1x3	0,6	1	0,50	2,0	2,0	8	3	M14x1	P	backlash free		
1112/0,5.8.80.138	8	0,5	40	16,5	21	0,40	1112	B	80	138	1x3	0,6	1	0,50	2,0	2,0	8	3	M14x1	P	backlash free		
1112/2.6.125.165	6	2	100	12,5	20	0,71	1112	B	125	165	1x3	1	1	1,08	1,5	1,5	6	2	M10x1	P	backlash free		
1112/2.6.65.105	6	2	40	12,5	20	0,71	1112	B	65	105	1x3	1	1	1,08	1,5	1,5	6	2	M10x1	P	backlash free		
1112/2.6.90.110	6	2	60	12,5	20	0,71	1112	A	90	110	1x3	1	1	1,08	1,5	1,5	6	2	M10x1	P	backlash free		
1112/2.6.95.135	6	2	70	12,5	20	0,71	1112	B	95	135	1x3	1	1	1,08	1,5	1,5	6	2	M10x1	P	backlash free		
1112/1.12.110.180	12	1	50	20,5	24	1,10	1112	B	110	180	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.12.160.230	12	1	100	20,5	24	1,10	1112	B	160	230	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.12.210.280	12	1	150	20,5	24	1,10	1112	B	210	280	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.12.260.330	12	1	200	20,5	24	1,10	1112	B	260	330	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.12.310.380	12	1	250	20,5	24	1,10	1112	B	310	380	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.12.355.397	12	1	300	20,5	24	1,10	1112	A	355	397	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.12.410.480	12	1	350	20,5	24	1,10	1112	B	410	480	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.12.510.580	12	1	450	20,5	24	1,10	1112	B	510	580	1x3	0,8	1	2,00	3,0	3,0	10	3	M18x1	P	backlash free		
1112/1.3.44.85	3	1	20	8,5	15	0,24	1112	B	44	85	1x2	0,8	1	0,25	1,0	1,0	5		M6	P	backlash free		
1112/1.3.64.105	3	1	40	8,5	15	0,24	1112	B	64	105	1x2	0,8	1	0,25	1,0	1,0	5		M6	P	backlash free		
1112/1.3.76.90	3	1	50	8,5	15	0,24	1112	A	76	90	1x2	0,8	1	0,25	1,0	1,0	5		M6	P	backlash free		
1112/1.3.94.135	3	1	70	8,5	15	0,24	1112	B	94	135	1x2	0,8	1	0,25	1,0	1,0	5		M6	P	backlash free		