

2412-Flange single nut



select	Inquiry Label		Static load capacity [kN]	Friction torque FROM [Ncm]	Friction torque TO [Ncm]	Pilot Length [mm]	Wiper extension [mm]	Flange thickness [mm]	Flange flat dimension [mm]	Pilot diameter tolerance [mm]	Flange hole diameter	Flange diameter [mm]	Accuracy	No. of starts	Ball diameter [mm]	Ball circles [mm]	dN [mm]	P [mm]	Nominal stroke [mm]	D1 [mm]	D4 [mm]	L [mm]	Dynamic load capacity [kN]	Series	Shaft style	Thread length [mm]	Overall length [mm]	Preload/backlash free/with backlash
2412/4.8.110.168	8	4	70	16	22	27	3,00	2412	B	110	168	1x5	1,5	1	3,60	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/4.8.140.198	8	4	100	16	22	27	3,00	2412	B	140	198	1x5	1,5	1	3,60	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/4.8.145.170	8	4	100	16	22	27	3,00	2412	A	145	170	1x5	1,5	1	3,60	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/4.8.190.248	8	4	150	16	22	27	3,00	2412	B	190	248	1x5	1,5	1	3,60	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/4.8.245.270	8	4	200	16	22	27	3,00	2412	A	245	270	1x5	1,5	1	3,60	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/4.8.80.138	8	4	40	16	22	27	3,00	2412	B	80	138	1x5	1,5	1	3,60	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/5.8.110.168	8	5	70	16	22	22	1,90	2412	B	110	168	1x3	1,5	1	2,10	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/5.8.140.198	8	5	100	16	22	22	1,90	2412	B	140	198	1x3	1,5	1	2,10	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/5.8.145.170	8	5	100	16	22	22	1,90	2412	A	145	170	1x3	1,5	1	2,10	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/5.8.190.248	8	5	150	16	22	22	1,90	2412	B	190	248	1x3	1,5	1	2,10	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/5.8.245.270	8	5	200	16	22	22	1,90	2412	A	245	270	1x3	1,5	1	2,10	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		
2412/5.8.80.138	8	5	40	16	22	22	1,90	2412	B	80	138	1x3	1,5	1	2,10	2,0	2,0		6	6	9,5	g6	3,4	28	P	backlash free		