

2422-Flange single nut



select	Inquiry Label		Static load capacity [kN]	Friction torque FROM [Ncm]	Friction torque TO [Ncm]	Pilot Length [mm]	Wiper extension [mm]	Flange thickness [mm]	Flange flat dimension [mm]	Lube hole [mm]	Pilot diameter tolerance [mm]	Flange hole diameter	Flange diameter [mm]	Accuracy	No. of starts	Ball diameter [mm]	dN [mm]	P [mm]	Nominal stroke [mm]	D1 [mm]	D4 [mm]	L [mm]	Dynamic load capacity [kN]	Series	Shaft style	Thread length [mm]	Overall length [mm]	Ball circles	Preload/backlash free/with backlash
2422/10.12.110.180	12	10	50	24	32	29	5,80	2422	B	110	180	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.12.160.230	12	10	100	24	32	29	5,80	2422	B	160	230	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.12.210.280	12	10	150	24	32	29	5,80	2422	B	210	280	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.12.260.330	12	10	200	24	32	29	5,80	2422	B	260	330	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.12.310.380	12	10	250	24	32	29	5,80	2422	B	310	380	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.12.355.397	12	10	300	24	32	29	5,80	2422	A	355	397	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.12.410.480	12	10	350	24	32	29	5,80	2422	B	410	480	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.12.510.580	12	10	450	24	32	29	5,80	2422	B	510	580	2+2	2,5	2	7,00	3,0	3,0	10	9	8	13		g6	4,5	40	P	backlash free		
2422/10.16.139.221	16	10	50	32	42	44	19,60	2422	B	139	221	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.189.271	16	10	100	32	42	44	19,60	2422	B	189	271	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.239.321	16	10	150	32	42	44	19,60	2422	B	239	321	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.289.371	16	10	200	32	42	44	19,60	2422	B	289	371	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.389.471	16	10	300	32	42	44	19,60	2422	B	389	471	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.470.527	16	10	400	32	42	44	19,60	2422	A	470	527	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.489.571	16	10	400	32	42	44	19,60	2422	B	489	571	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.689.771	16	10	600	32	42	44	19,60	2422	B	689	771	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/10.16.889.971	16	10	800	32	42	44	19,60	2422	B	889	971	3+3	3,5	2	27,70	4,0	4,0	13	12	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.139.221	16	16	50	32	42	41	13,40	2422	B	139	221	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.189.271	16	16	100	32	42	41	13,40	2422	B	189	271	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.239.321	16	16	150	32	42	41	13,40	2422	B	239	321	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.289.371	16	16	200	32	42	41	13,40	2422	B	289	371	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.389.471	16	16	300	32	42	41	13,40	2422	B	389	471	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.470.527	16	16	400	32	42	41	13,40	2422	A	470	527	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.489.571	16	16	400	32	42	41	13,40	2422	B	489	571	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.689.771	16	16	600	32	42	41	13,40	2422	B	689	771	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/16.16.889.971	16	16	800	32	42	41	13,40	2422	B	889	971	2+2	3,5	2	18,30	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/20.16.139.221	16	20	50	32	42	48	13,00	2422	B	139	221	2+2	3,5	2	17,90	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/20.16.189.271	16	20	100	32	42	48	13,00	2422	B	189	271	2+2	3,5	2	17,90	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/20.16.239.321	16	20	150	32	42	48	13,00	2422	B	239	321	2+2	3,5	2	17,90	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		
2422/20.16.289.371	16	20	200	32	42	48	13,00	2422	B	289	371	2+2	3,5	2	17,90	4,0	4,0	13	10	10	20	M6x1	g6	5,5	52	P	backlash free		