

Nut with ETA+ Technology



select	Inquiry Label	Max. preload [kN]	Friction torque FROM [Ncm]	Friction torque TO [Ncm]	Pilot length [mm]	Wiper extension [mm]	Flange thickness [mm]	Flange flat dimension [mm]	Wiper extension [mm]	Additional wiper extensions for combination wipers [mm]	Lube hole [mm]	Pilot diameter tolerance [mm]	Flange hole diameter	Flange diameter [mm]	Stiffness [N/μm]	Static load capacity [kN]	S*	ETA+	dN [mm]	P	D1	D4	L	Dynamic load capacity [kN]	DN-value	Series	Ball circles	Ball diameter [mm]	No. of starts	Accuracy
1516/10.32.6.3E		□	32	10	50	65	130	40,30	120000	1516	3+3	6	1	49,70	540	4,03	12,9	38,7	16	7	12	31	7	10	M6x1	g6	9	80	P	
1516/10.32.6.4E		□	32	10	50	65	140	51,60	120000	1516	4+4	6	1	66,30	710	5,16	16,5	49,5	16	7	12	31	7	10	M6x1	g6	9	80	P	
1516/10.32.6.5E		□	32	10	50	65	187	62,60	120000	1516	2x5	6	1	82,90	880	6,26	24,0	56,1	16	7	12	31	7	10	M6x1	g6	9	80	P	
1516/10.50.7.5.3E		□	50	10	75	93	138	69,50	120000	1516	3+3	7,5	1	101,50	890	6,95	45,2	93,8	16	7	16	42,5	7	10	M8x1	g6	11	110	P	
1516/10.50.7.5.4E		□	50	10	75	93	159	89,00	120000	1516	4+4	7,5	1	135,40	1180	8,9	57,8	120,1	16	7	16	42,5	7	10	M8x1	g6	11	110	P	
1516/10.63.7.5.4E		□	63	10	90	108	162	100,70	120000	1516	4+4	7,5	1	175,00	1460	10,07	88,8	164,9	16	7	18	47,5	7	10	M8x1	g6	11	125	P	
1516/10.63.7.5.5E		□	63	10	90	108	182	122,00	120000	1516	5+5	7,5	1	218,80	1800	12,2	107,6	199,8	16	7	18	47,5	7	10	M8x1	g6	11	125	P	
1516/15.40.7.5.3E		□	40	15	63	78	180	60,10	120000	1516	2x3	7,5	1	77,50	630	6,01	28,8	67,3	16	7	14	35	7	10	M8x1	g6	9	93	P	
1516/15.63.9.4E		□	63	15	95	115	239	150,30	120000	1516	2x4	9	1	261,20	1590	15,03	132,6	246,2	25	7	20	50	7	10	M8x1	g6	13,5	135	P	
1516/20.80.11.4E		□	80	20	125	145	284	221,50	120000	1516	2x4	11	1	411,50	2000	22,15	265,8	443,0	25	7	25	65	7	10	M8x1	g6	13,5	165	P	
1516/5.25.3.5.3E	□	□	25	5	40	51	76	18,10	120000	1516	3+3	3,5	1	23,40	460	1,81	1,8	16,3	10	6	10	24	6	9	M6x1	g6	6,6	62	P	
1516/5.25.3.5.4E		□	25	5	40	51	90	23,10	120000	1516	4+4	3,5	1	31,20	610	2,31	5,8	17,3	10	6	10	24	6	9	M6x1	g6	6,6	62	P	
1516/5.25.3.5.5E		□	25	5	40	51	107	28,00	120000	1516	5+5	3,5	1	39,00	750	2,8	7,0	21,0	10	6	10	24	6	9	M6x1	g6	6,6	62	P	
1516/5.32.3.5.3E	□	□	32	5	50	65	78	21,30	120000	1516	3+3	3,5	1	32,40	610	2,13	6,8	20,4	10	6	12	31	6	9	M6x1	g6	9	80	P	
1516/5.32.3.5.4E		□	32	5	50	65	92	27,30	120000	1516	4+4	3,5	1	43,20	800	2,73	8,7	26,2	10	6	12	31	6	9	M6x1	g6	9	80	P	
1516/5.40.3.5.3E		□	40	5	63	78	79	23,80	120000	1516	3+3	3,5	1	41,50	750	2,38	9,5	28,6	10	6	14	35	6	9	M8x1	g6	9	93	P	
1516/5.50.3.5.4E		□	50	5	75	93	93	34,00	120000	1516	4+4	3,5	1	70,80	1190	3,4	17,0	51,0	10	6	16	42,5	6	9	M8x1	g6	11	110	P	
1516/5.50.3.5.5E		□	50	5	75	93	103	41,20	120000	1516	5+5	3,5	1	88,50	1470	4,12	24,7	57,7	10	6	16	42,5	6	9	M8x1	g6	11	110	P	
1516/10.50.7.5.5E		□	50	10	75	93	191	107,80	120000	1516	2x5	7,5	1	169,20	1460	10,78	75,5	140,1	16	7	16	42,5	7	10	M8x1	g6	11	110	P	
1516/10.80.7.5.6E		□	80	10	105	125	215	165,90	120000	1516	2x6	7,5	1	357,10	2670	16,59	199,1	331,8	16	7	20	55	7	10	M8x1	g6	13,5	145	P	
1516/5.20.3.5.3E		□	20	5	36	47	85	15,90	82000	1516	2x3	3,5	1	18,20	370	1,59	1,3	11,4	10	6	10	22	6	9	M6	g6	6,6	58	P	
1516/5.20.3.5.4E		□	20	5	36	47	95	20,40	82000	1516	2x4	3,5	1	24,30	490	2,04	1,6	14,7	10	6	10	22	6	9	M6	g6	6,6	58	P	
1516/15.40.7.5.4E		□	40	15	63	78	211	76,90	120000	1516	2x4	7,5	1	103,40	830	7,69	40,0	83,1	16	7	14	35	7	10	M8x1	g6	9	93	P	
1516/5.16.3.5.3E		□	16	5	28	38	85	13,20	120000	1516	2x3	3,5	1	13,10	270	1,32	0,8	7,6	10	6	10	20	6	9	M6x1	g6	5,5	48	P	
2526/10.20.3.5.5E		□	20	10	36	47	69	25,20	160000	2526	5+5	3,5	2	32,50	590	2,52	5,0	15,1	16	7	10	22	7	-	M6x1	g6	6,6	58	P	
2526/15.25.3.5.3E	□	□	25	15	40	51	63	16,70	160000	2526	3+3	3,5	2	22,20	390	1,67	1,7	15,0	16	7	10	24	7	-	M6x1	g6	6,6	62	P	
2526/20.20.3.5.2E		□	20	20	36	47	57	9,30	160000	2526	2+2	3,5	2	10,50	150	0,93	0,7	6,7	16	7	10	22	7	-	M6x1	g6	6,6	58	P	
2526/20.20.3.5.3E		□	20	20	36	47	77	14,50	160000	2526	3+3	3,5	2	17,40	220	1,45	1,2	10,4	16	7	10	22	7	-	M6x1	g6	6,6	58	P	
2526/20.25.3.5.3E	□	□	25	20	40	51	77	16,90	160000	2526	3+3	3,5	2	22,90	330	1,69	1,7	15,2	16	7	10	24	7	-	M6x1	g6	6,6	62	P	
2526/10.25.3.5.5E		□	25	10	40	51	69	28,00	160000	2526	5+5	3,5	2	40,40	750	2,8	7,0	21,0	16	7	10	24	7	-	M6x1	g6	6,6	62	P	