

Flange single nut



select	Inquiry Label		dN [mm]	P [mm]	i Ball circles	LF [mm]	ø D1 [mm]	Dyn. load capacity [kN]	Stat. load capacity [kn]
8436/5.16.3,5.3	16	5	3	46	28	10.1	12		
2446/10.16.3,5.6	16	10	3 + 3	44	32	19.6	27.4		
8436/5.20.3,5.3	20	5	3	46	36	12.1	16.7		
2446/10.20.3,5.6	20	10	3 + 3	49	36	22.8	36.5		
2446/20.20.3,5.4	20	20	2 + 2	57	36	14.7	22.4		
8436/5.25.3,5.3	25	5	3	46	40	13.7	21.5		
2446/10.25.3,5.6	25	10	3 + 3	49	40	25.2	45.4		
2446/20.25.3,5.4	25	20	2 + 2	57	40	17.1	29.5		
2446/25.25.3,5.4	25	25	2 + 2	66	40	16.7	29		
8436/5.32.3,5.4	32	5	4	53	50	20.4	39.8		
8436/10.32.6.3	32	10	3	72	50	30.8	45.6		
3446/20.32.6.4	32	20	2 + 2	68	56	39.3	63.6		
3446/32.32.6.2	32	32	1 + 1	60 + 2x5*	56	18.2	26.5		
8436/5.40.3,5.5	40	5	5	60	63	27.5	63.6		
8436/10.40.7,5.4	40	10	4	84	63	59	95.1		
3446/20.40.6.6	40	20	3 + 3	89	63	64.9	126.3		
3446/40.40.7,5.4	40	40	2 + 2	107	70	59	96.6		
8436/10.50.7,5.4	50	10	4	86	75	67.4	124.3		
8446/20.50.7,5.6	50	20	3 + 3	90	75	84	154.4		
8436/10.63.7,5.5	63	10	5	98	90	91.8	201.1		

Flange single nut

3446/20.63.7,5.6	63	20	3 + 3	91	95	107.6	249.1	
8436/10.80.7,5.6	80	10	6	110	105	123.8	328.6	