

Rotating Nuts



select	Inquiry Label	Friction torque FROM [Ncm]	Friction torque TO [Ncm]	Pilot Length [mm]	Thread length [mm]	Wiper extension [mm]	Flange thickness [mm]	Additional wiper extensions [mm]	Additional wiper extensions for combination wipers [mm]	Pilot diameter tolerance [mm]	Thread diameter [mm]	Diameter for wiper extension [mm]	Flange hole diameter	Max. preload [kN]	Stiffness [N/μm]	dN [mm]	P [mm]	D1 [mm]	D4 [mm]	L [mm]	Dynamic load capacity [kN]	DN-value	Series	Ball circles	Ball diameter [mm]	No. of starts	Static load capacity [kN]	Flange diameter [mm]
1414/10.32.6.5	32	10	50	65	104	47,80	120000	1414	1x5	6	1	76,00	490	3,824	29,4	68,5	34	20	7	12	0	10	h5	M50x1,5	50	M6	80	
1414/10.50.7.5.6	50	10	80	93	120	95,60	120000	1414	1x6	7,5	1	186,50	990	7,648	107,1	198,8	45	23	7	16	0	10	h5	M80x2	75	M8	110	
1414/10.63.7.5.6	63	10	90	108	120	107,40	120000	1414	1x6	7,5	1	241,30	1230	8,592	151,6	281,5	55	25	7	18	0	10	h5	M90x2	85	M10	125	
1414/15.40.7.5.4	40	15	70	78	117	58,70	120000	1414	1x4	7,5	1	94,80	460	4,696	48,8	101,4	45	23	7	14	0	10	h5	M70x2	65	M6	93	
1414/15.63.9.4	63	15	100	115	131	116,70	120000	1414	1x4	9	1	239,90	940	9,336	164,7	305,8	55	25	7	20	0	10	h5	M100x2	95	M10	135	
1414/5.25.3.5.5	25	5	40	51	72	21,20	120000	1414	1x5	3,5	1	35,90	430	1,696	8,5	25,4	34	20	7	10	0	9	h5	M40x1,5	40	M6	62	
1414/5.32.3.5.6	32	5	50	65	74	29,00	120000	1414	1x6	3,5	1	59,60	680	2,320	14,8	44,5	34	20	7	12	0	9	h5	M50x1,5	50	M6	80	
3424/20.32.6.6	32	20	60	71	88	57,90	160000	3424	3+3	6	2	100,00	530	4,632	35,6	83,0	45	20	7	14	0	10	h5	M60x2	60	M6	86	
3424/20.40.6.8	40	20	70	78	109	84,70	160000	3424	4+4	6	2	172,20	960	6,776	75,9	140,9	45	23	7	14	0	10	h5	M70x2	65	M6	93	
3424/25.40.6.6	40	25	70	78	107	64,30	160000	3424	3+3	6	2	125,40	630	5,144	53,5	111,1	45	23	7	14	10	20	h5	M70x2	65	M6	93	
3424/25.50.7.5.8	50	25	90	108	130	126,60	160000	3424	4+4	7,5	2	269,10	1180	10,128	141,8	263,3	55	25	7	18	10	20	h5	M90x2	85	M10	125	
3424/25.60.9.8	60	25	100	115	131	214,50	160000	3424	4+4	9	2	492,90	1790	17,160	308,6	514,3	55	25	7	20	10	20	h5	M100x2	95	M10	135	
3424/30.50.7.5.6	50	30	90	108	120	96,30	160000	3424	3+3	7,5	2	196,30	800	7,704	107,9	200,3	55	25	7	18	10	20	h5	M90x2	85	M10	125	
3424/30.60.9.8	60	30	100	115	151	213,50	160000	3424	4+4	9	2	491,00	1650	17,080	308,4	514,0	55	25	7	20	10	20	h5	M100x2	95	M10	135	
3424/40.50.7.5.6	50	40	90	108	149	94,60	160000	3424	3+3	7,5	2	193,60	640	7,568	105,9	196,8	55	25	7	18	10	20	h5	M90x2	85	M10	125	
3424/40.60.9.6	60	40	100	115	150	161,50	160000	3424	3+3	9	2	356,70	1040	12,920	232,6	387,6	55	25	7	20	10	20	h5	M100x2	95	M10	135	